

# GEORIG 620

## TECHNICAL SPECIFICATIONS

<b>Kinematics</b>	<ul style="list-style-type: none"> <li>• Base rotation on truck</li> <li>• Mast lifting -5° + 90°</li> <li>• Mast inclination ( left -right +/-15°)</li> <li>• 4 stabilizers</li> <li>• Back feed 800 mm</li> </ul>
-------------------	---

## CRAWLER

<b>Type</b>	Fix truck with 360° rotation
<b>Pads</b>	Steel or rubber
<b>Wheel base</b>	1400 mm
<b>Lenght</b>	mm
<b>Track width</b>	300-400 mm
<b>Weight</b>	6000 Kg (depending on accessories)
<b>Speed</b>	0-2 Km/h

## HYDRAULIC CIRCUIT

<b>Controls</b>	Radio controlled, proportional, load sensing
<b>Pump</b>	Piston type, variable displacement
<b>Max Oil flow</b>	150 lt/min max
<b>Max Pressure</b>	200 bar max

## ENGINE

<b>Type</b>	Diesel turbo
<b>Model</b>	Kubota V3307 Stage V
<b>Power</b>	55,6Kw – 74 Hp

## DRILL MAST

<b>Model</b>	S 300
<b>Stroke</b>	Standard 2300
<b>Pull back / down</b>	4.500 Kg