

# RLD 2

## TECHNICAL SPECIFICATIONS

<b>Lenght</b>	5200 mm
<b>Width</b>	4100 mm
<b>Height</b>	2000mm
<b>Weight</b>	9 ton

## UNDERCARRIAGE

<b>Type</b>	Fixed
<b>Shoe</b>	300mm
<b>Overall lenght</b>	2081mm
<b>Overall width</b>	2000mm
<b>Max speed</b>	2 km/h

## ENGINE

<b>Model</b>	Deutz DTCD 3.6 stage 4 or Kubota 3800 V stage 3B
<b>Max output</b>	(130 HP) 99 kW (115 HP)

## HYDRAULIC SYSTEM

<b>Pump</b>	Piston type, variable flow LS (Hawe 110 cc)
<b>Max flow</b>	240 lt min
<b>Max pressure</b>	170 bar

## DRILL MAST

<b>Model</b>	SPEEDY 180 S
<b>Fioretto di partenza</b>	4.8 mt

## DRIFTER

<b>Model</b>	Doofer 430X or 530X
<b>Shank</b>	22x108
<b>Weight</b>	50 kg
<b>Cradle</b>	With shock absorber

## CONTROLS

<b>Positioning</b>	Remote, located on the left side
<b>Drilling</b>	Remote, located on the left side
<b>Track</b>	Remote, located on the back side

## KINEMATICS

<b>Rail</b>	4 mt ( useful 3,5 mt)
<b>Base slew ring</b>	360°
<b>Inclination drill mast</b>	+ - 20°
<b>Lateral inclinat. Drill mast</b>	+ - 25°
<b>Backfeed</b>	550mm
<b>Zoom</b>	200mm
<b>Stabilizers</b>	2 +2