

# S321 PROBE DRILL MAST

## TECHNICAL SPECIFICATIONS

<b>Drill mast</b>	S321 Gear Box
<b>Stroke</b>	Stand 3350 mm ( other strokes on request)
<b>Pull back / down</b>	4.500 Kg ( option 6.500 Kg)
<b>Hydraulics</b>	6 proportional valves for rotation / percussion / feed / clamp + clamp + break are included ( other valves available as option for TBM movement )
<b>Controls</b>	Radio remote control and LCD screen for diagnostic and setting
<b>Data log</b>	On request
<b>Hoses</b>	Side catenary included for drill mast

## DRILL MAST ACCESSORIES AND OPTIONS

<b>Clamp and break device</b>	55-152; 55-180; 55-200
<b>Slidramatic</b>	Rotary head lateral movement
<b>Winch</b>	800 kg winch with pulley (other options available on request)

## SAFETY GARD OPTIONS

<b>Manual</b>	Manual opening type
<b>Electronic</b>	Electronic front guard and lateral steel guard
<b>Hydraulic</b>	Corner opening hydraulic type

## ROTARY HEADS AND DRIFTERS

<b>Rotary head</b>	RP500 / RP 800 / RH6
<b>Drifters</b>	<ul style="list-style-type: none"> <li>• EURODRILL RH4 X ; RH6 X</li> <li>• Floating spindle kit for DTH available</li> </ul>

